

MIGRATORY CORROSION INHIBITOR (MCI®) PRODUCTS FOR CONCRETE



MCI®-2005 NS



PRODUCT DESCRIPTION

MCI®-2005 NS (normal set) is a liquid concrete admixture that protects steel reinforcing, carbon steel, galvanized steel and other metals embedded in concrete from corrosion induced by carbonation, chloride and atmospheric attack without changing the set time of most concrete mixes. MCI®-2005 NS protects by a time-proven migratory corrosion inhibitor function. In addition, it contains a proven contact inhibitor. When incorporated into the concrete mix, Migrating Corrosion Inhibitors (MCI®) seek out and form a corrosion inhibiting protective layer on metals. When used with repair mortars and grouts, MCI®-2005 NS will migrate to undisturbed concrete providing effective corrosion protection to rebar already in place.

FEATURES

MCI®-2005 NS offers engineers, owners, contractors, DOTs and government agencies a time-proven corrosion inhibiting technology that will extend the life of all reinforced concrete structures.

- Protects against the harmful effects of corrosion in different types of concrete
- Required dosage is not affected by the chloride concentration
- Does not contain calcium nitrite

- Non-hazardous and non-toxic
- Safe and environmentally friendly
- Technology is lab and field proven worldwide
- Concentrated for cost effectiveness on all projects
- Protects both anodic and cathodic areas
- Will migrate to adjacent areas to protect metals

TYPICAL USES

MCI®-2005 NS is recommended for:

- All reinforced, precast, prestressed, post-tensioned or marine concrete structures
- Steel-reinforced concrete bridges, highways and streets exposed to corrosive environments (carbonation, deicing salts and atmospheric attack)
- Parking decks, ramps and garages
- All reinforced marine concrete structures
- Concrete piers, piles, pillars, pipes and utility poles
- Restoration and repair of all reinforced concrete commercial and civil engineered structures
- Can be added either to the water or powder on-site for shotcreting applications
- Can be added into a manufacturer's repair mortar formulation to enhance its corrosion protection ability
- NSF Standard 61 approved for potable water applications (certified by Underwriters Laboratories)

DOSAGE

Add MCI®-2005 NS to concrete mix at the rate of 1.5 pts/yd³ (1l/m³).

APPLICATION

MCI®-2005 NS can be added to the mix water or to concrete powder at the ready-mix plant, directly into a ready-mix truck drum or in portable mixers. Concrete should be mixed thoroughly.



TYPICAL PROPERTIES

Appearance	Dark brown liquid
pH	11-12 (1% solution)
Non-volatile Content	25-30%
Density	9.9-10 lb/gal (1.19-1.20 kg/l)

PACKAGING AND STORAGE

MCI®-2005 NS is available in 5 gallon (19 liter) pails, 55 gallon (208 liter) drums, liquid totes and bulk. The shelf life is 24 months in a sealed container. Do not allow product to freeze.

FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Distributed by:



4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.CortecVCI.com>